AITCHSON® TRANSFER ROLLER®



TOUGH

RELIABLE

UNIQUE



SUPERIOR PASTURE ROLLERS



QUALITY PRODUCTS BUILT TO LAST!

AITCHISON

TECHNICAL SPECIFICATIONS TRANSFER ROLLERS

TR 240

TR 275



WORKING WIDTH
TRANSPORT WIDTH
ROLLER DIAMETER
WEIGHT-DRY
WEIGHT-WET
WORKING SPEED
3PT LINK
TRACTOR HP-4WD

2.40 M (8') 2.65 M 600 mm 825 KG (1815 lbs) 1675 KG (3685 lbs) 1-15 KPH HYDRAULIC 60-120 HP 2.75 M (9'2") 3.00 M 600 mm 945 KG (2079 lbs) 1920 KG (4224 lbs) 1-15 KPH HYDRAULIC 80-150 HP



- Unique weight transfer system to increase and decrease downward pressure on the roller
- Tractor weight can be transferred onto the roller making it a true heavy weight plus it reduces tractor tyre ruts
- · Easy downward pressure adjustment from the tractor seat
- · Effective on both wet and dry pastures
- Rolling effectively kills grassgrub, repairs pugging, pushes in stones, makes pasture more mower and rake friendly, and consolidates peat land
- · Rugged maintenance free construction

specifications are subject to change without prior notice

enquire now from your authorised dealer



FOR YOUR NEAREST DEALER AND FURTHER INFORMATION CONTACT:

New Zealand

REESE ENGINEERING LTD,
PALMERSTON NORTH, NEW ZEALAND.
Tel: 06 357 9323.
Fax: 06 354 3155.
email: reese@xtra.co.nz.
VISIT OUR WEBSITE: www.reese.co.nz
www.aitchison.co.nz

Australi

REESE ENGINEERING LTD,
GEELONG, VICTORIA, AUSTRALIA
FREEPHONE 1-800-140-196
FREEFAX 1-800-140-195
email: reese@xtra.co.nz.
VISIT OUR WEBSITE: www.reese.co.nz
www.aitchison.co.nz