

REAP THE BENEFITS
EVERY TIME WITH THE
SEEDMATIC® SERIES



4124CT Model Shown



4124CT Model Shown



enquire now from your authorised dealer

AITCHISON

QUALITY PRODUCTS BUILT TO LAST

www.aitchsionagri.com

NEW ZEALAND:

41 Kelvin Grove Road, P.O. Box 5056, Palmerston North New Zealand.
Tel: +64 6 357 9323 Fax: +64 6 354 3155

AUSTRALIA

Tel: 1 800 140 196 Fax: 1 800 140 195 mob: 0400 540 300

AITCHISON

SEEDMATIC

SOWING
THE
SEEDS

THE ONLY
SEEDMATIC
DRILLS YOU'LL
PUT OUT TO
PASTURE

A PRODUCT OF NEW ZEALAND



AITCHISON

SEEDMATIC

Built with over five decades of proven Aitchison® seeding experience in mind, the extremely successful 4000 Series Seedmatic® seed drill lets you sow the seeds of success, the Aitchison zero-tillage way.

The Seedmatic tine drills will penetrate existing pastures, hard and rocky as well as cultivated soils. They are commonly used to renovate or bulk up existing pastures, as well as sow crops such as wheat and clover, peas or canola into cultivated soils or maize stubble.

Renowned for building soil organic matter and creating an optimal environment for trouble free seed germination. The Seedmatic drills have a narrow 125mm or 5inch row spacing with 14inch disc coulters combined with and a 400mm stagger of seeding rows enabling superior residual matter clearance. The vibrating 25mm Seedmatic tines are designed with a slimline boot holder to handle trash with ease and together with the Aitchison tungsten tipped Ni-hard inverted “T” boot, create the perfect seeding environment.

The Seedmatic drill range is designed to deliver uniform plant emergence with optimum yields at lower costs. The unique seeding system is extremely accurate, and the infinitely variable gearbox handles most seed volumes and sizes effortlessly.

The 4000 Series Seedmatic is also available as a disc version drill and fitted with a large 406mm (16”) concave disc opener & heavy dragarm which are good for extreme stone or rocky situations, or difficult matting type swards such as Kikuyu and high crop residue situations like maize stubble.



TINE DRILLS SEED & FERTILISES MODELS

SPECIFICATIONS	4120C(T)	4124C(T)	4128CT
Overall Width	2.92 m (9' 6")	3.42 m (11' 2")	3.92 m (12' 10")
Sowing Width	2.50 m (8' 2")	3.0 m (9' 10")	3.50 m (11' 5")
Overall Height	1.75 m (5' 9")	1.75 mm (5' 9")	1.75 mm (5' 9")
Weight Empty (non-trailed)	1460 kg / 3219 lb	1620 kg / 3572 lb	-
Weight Empty (trailed) (T)	1730kg / 3814 lb	1910 kg / 4211 lb	2050 kg / 4520 lb
Seed Hopper Capacity	475 lt (13.5 bu)	570 lt (16.1 bu)	665 lt (18.8 bu)
Fertiliser Box Capacity	490 lt (13.9 bu)	590 lt (16.7 bu)	690 lt (19.5 bu)
No of Rows	20	24	28
Row Spacing	125mm (5")	125mm (5")	125mm (5")
Frame Stagger	410mm	410mm	410mm
Transport Kit (T)	optional	optional	✓
Tow Hitch	(standard with Transport Kit Only)		✓

SOW YOUR SEEDS IN ANY CONDITION WITH THE WORLD'S MOST VERSATILE RANGE OF DRILLS

TINE DRILLS SEED ONLY MODELS

SPECIFICATIONS	4020C(T)	4024C(T)	4028CT
Overall Width	2.92 m (9' 6")	3.42 m (11' 2")	3.92 m (12' 10")
Sowing Width	2.50 m (8' 2")	3.0 m (9' 10")	3.50 m (11' 5")
Overall Height	1.81 m (5' 11")	1.81 m (5' 11")	1.81 m (5' 11")
Weight Empty (non-trailed)	1280 kg / 2822 lb	1440 kg / 3175 lb	-
Weight Empty (trailed) (T)	1570 kg / 3462 lb	1730 kg / 3814 lb	1870kg / 4123 lb
Seed Hopper Capacity	700 lt (19.8 bu)	850 lt (24.1 bu)	1000 lt (28.3 bu)
No of Rows	20	24	28
Row Spacing	125mm (5")	125mm (5")	125mm (5")
Frame Stagger	410mm	410mm	410mm
Transport Kit (T)	optional	optional	✓
Tow Hitch	(standard with Transport Kit Only)		✓

